

INSPIRE 980

Integrated Amplifier



This 80 watt per channel integrated amplifier takes all the features of the Inspire 880 and extends them even further by adding network capability.

Wired or wireless Ethernet allows you to access your music library stored on a networked drive and control your playback.

Various network controllers can be used but for the ultimate in refinement of interfaces the Plinius Arataki can't be beaten. This iPad app allows you to connect and control the music in your library and enjoy all the emotions you remember from

the first time you heard your favourite tunes.

Like the 880, the Inspire 980 retains USB capability, two optical inputs, three line inputs (including Balanced XLR) and an on-board phono stage – all providing the flexibility to connect to virtually any source.

The aesthetic designs of the Inspire range introduce new

tones and textures to the finishes that reflect the position these integrated units have in the Plinius range.

Whether enjoying a listening session with friends or using a play-list for background music at a party, the Inspire 980 and the Arataki controller are the perfect combo for enjoying music in high fidelity.

PLINIUS

The heart of music
www.pliniusaudio.com

INSPIRE 980

Integrated Amplifier



POWER

80 watts RMS per channel into 8 ohms.
Both channels driven from 20Hz to 20kHz at less than 0.2% total harmonic distortion

FREQUENCY RESPONSE

20Hz to 20kHz ± 0.2 dB
-3dB at 2Hz and -3dB at 300kHz

DISTORTION

Typically $< 0.05\%$ THD at rated power
0.2% THD and IM worst case prior to clipping

CURRENT OUTPUT

16A short duration peak per channel
Fuse protected

INPUT IMPEDENCE

10k ohms for line inputs

GAIN

Line inputs to speaker out: 38dB

DIGITAL INPUTS

1 x USB asynchronous
(up to 24 bit, 192ks/s)
2 x Optical Toslink
(up to 24 bit, 96ks/s)

PHONO INPUT

RCA Unbalanced Input
Gain: 50dB
Load: 47k
Frequency Response: 20Hz to 20kHz
 ± 0.2 dB within RIAA spec

DLNA DIGITAL AUDIO RENDERER

DLNA 1.0/1.5 compatible

SUPPORTED AUDIO FILE SERVER

DLNA Digital Media Servers

SUPPORTED PLAYBACK CONTROL

DLNA Digital Media Controllers
DLNA Mobile Digital Media Controllers
UPnP smartphone applications
iPad/iPod applications

AUDIO CODEC SUPPORT

FLAC (up to 24 bit, 192ks/s), LPCM
(up to 24 bit, 192ks/s), ALAC, AIFF, MP3

INPUT

1 x RJ45 connector

CONNECTIVITY

10/100 Ethernet
Wi-Fi

POWER/CURRENT CONSUMPTION

300W
0.14A (32W) Standby

DIMENSIONS

Height: 72mm (3")
Width: 450mm (17.75")
Depth: 350mm (13.75")
Weight: 10kg (22lb)

PRODUCT FEATURES

Available in black or silver



PLINIUS

The heart of music
www.pliniusaudio.com