REFERENCE M-10

Dual Mono Preamplifier



The Reference M-10 is an entirely new, fully discrete, dual mono preamplifier, designed from the ground up. It is the culmination of decades of experience and the constant pursuit of excellence in electronic design.

The Reference M-10 is testament to Plinius' relentless quest to produce a preamplifier that reveals extraordinary audio detail. At this crucial beginning of the signals journey low value, audio grade resistors are used to minimise noise and, when combined with the adjustable gain feature result in sound without

distortion or unnecessary colour, this is pure, powerful sound.

Plinius' signature aesthetic is still ever present in the external styling of both the dual mono preamplifier and it's remote.
As always, form follows function resulting in the ultimate in design sophistication.

Lovers of high-end audio reproduction will be impressed with the Reference M-10's uninhibited ability to supply pure detail to the matching Reference A-300 power amplifier. We believe the Reference M-10 can hold its head up amongst the world's best performing preamplifiers.



REFERENCE M-10

Dual Mono Preamplifier



DISTORTION <0.001% THD+N

FREQUENCY RESPONSE 20Hz to 20kHz +/-0.1dB

GAIN

INPUTS

High: 12dB (4x) Low: 0dB (1x)

3 x XLR/RCA selectable
3 x dedicated RCA
1 x HT Bypass XLR/RCA selectable

OUTPUTS
2 x XLR/RCA Pre-Out
1 x RCA Line Out

CONNECTIVITY
2 x Trigger Out
1 x Trigger In
1 x RC5 In

INPUT IMPEDANCE 7.5kΩ RCA/Unbalanced 47kΩ XLR/Balanced

MAXIMUM INPUT
7V RMS RCA/Unbalanced
7V RMS XLR/Balanced

PRE OUT SOURCE IMPEDENCE 10Ω RCA/Unbalanced 20Ω XLR/Balanced

MAXIMUM OUTPUT LEVEL 7V RMS RCA/Unbalanced 14V RMS XLR/Balanced

 DIMENSIONS

 Height:
 170mm
 (6.75")

 Width:
 510mm
 (20")

 Depth:
 480mm
 (19")

16kg

Weight:

RMS XLR/Balanced



